NSN 5306-01-327-5687

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-327-5687						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.553 inches and 0.603 inches						
Fastener Length:						
Between 2.251 inches and 2.281 inches						
Head Style:						
Dished hexagon						
Head Height:						
Between 0.188 inches and 0.203 inches						
Width Between Flats:						
Between 0.554 inches and 0.564 inches						
Grip Diameter:						
Between 0.3740 inches and 0.3745 inches						
Thread Diameter:						
0.375 inches						
Grip Length:						
Between 1.678 inches and 1.698 inches						
Thready Qty Per Inch (tpi):						
24						
Min. Tensile Strength (psi):						
160000 pounds per square inch						
Surface Finish:						
32.0 microinches threads						
Product Name:						
Navy special project						
Material:						
Iron alloy 660						
Material Specification:						
Material Specification: Ams 5731 assn standard single material response or ams5737 assn standard single material response						
Ams 5731 assn standard single material response or ams5737 assn standard single material response						
Ams 5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment:						
Ams 5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate						
Ams 5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:						
Ams 5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response						
Ams 5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:						
Ams 5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf						
Ams 5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data:						

N/a

NSN 5306-01-327-5687

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0