## NSN 5306-01-327-7640

Shear Bolt - Page 1 of 2

Unjf



specification 1st material response

View Online at https://aerobasegroup.com/nsn/5306-01-327-7640

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.947 inches
Fastener Length:
Between 3.557 inches and 3.572 inches
Head Style:
Spline extended washer
Head Height:
1.434 inches
Extended Washer Diameter:
2.495 inches
Extended Washer Thickness:
0.335 inches
Grip Diameter:
Between 1.498 inches and 1.499 inches
Head Minor Diameter:
1.625 inches
End Application:
Ch-47d, helicopter, cargo-trns.
Thread Diameter:
1.500 inches
Grip Length:
Between 1.615 inches and 1.625 inches
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
1800 megapascals
Minimum Yield Strength:
1020 megapascals
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military
Surface Treatment:
Cadmium
Surface Treatment Specification:
As672 national specification 11th treatment response
Thread Series Designator:

## NSN 5306-01-327-7640

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-s-5000 spec.

