## NSN 5306-01-327-8662

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-327-8662

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.594 inches
Fastener Length:
Between 1.267 inches and 1.297 inches
Head Style:
Dished hexagon
Head Height:
Between 0.219 inches and 0.234 inches
Width Between Flats:
Between 0.679 inches and 0.690 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon corners
Surface Finish:
63.0 microinches grip
Material:
Steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

## NSN 5306-01-327-8662

Shear Bolt - Page 2 of 2

A003b0



Thread Series Designator:
Unjf
Specification Data:
80205-nas1307 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: