
NSN 5306-01-327-9036

Shear Bolt - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.367 inches

Fastener Length:

Between 0.977 inches and 1.007 inches

Head Style:

Spline extended washer

Head Height:

Between 0.195 inches and 0.215 inches

Extended Washer Diameter:

Between 0.349 inches and 0.359 inches

Extended Washer Thickness:

Between 0.017 inches and 0.037 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Head Minor Diameter:

0.253 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2220000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-327-9036

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

