NSN 5306-01-328-9219

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-328-9219

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.345 inches
Fastener Length:
Between 1.018 inches and 1.048 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Special Features:
Dye threads only green
Color:
Green threads
Green threads Material:
Material:
Material: Iron alloy 660
Material: Iron alloy 660 Material Specification:
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response

80205-nas6708 professional/industrial association standard

NSN 5306-01-328-9219

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0