## NSN 5306-01-329-4135

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-329-4135

Thread Class
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.528 inches
Fastener Length:
Between 0.763 inches and 0.793 inches
Head Style:
Dished hexagon
Head Height:
Between 0.250 inches and 0.265 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Hole Diameter:
0.075 inches
Grip Diameter:
Between 0.4990 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6308 professional/industrial association standard

## NSN 5306-01-329-4135

Shear Bolt - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0