NSN 5306-01-329-7659

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-329-7659

Thread Class:
3a
Sa Thread Direction:
Right-hand
Thread Length:
0.446 inches
Fastener Length:
Between 1.056 inches and 1.086 inches
Head Style:
Double hexagon extended washer
Head Height:
Between 0.240 inches and 0.260 inches
Width Between Flats:
0.318 inches
Extended Washer Diameter:
Between 0.460 inches and 0.470 inches
Extended Washer Thickness:
Between 0.026 inches and 0.046 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Aluminum and chromate
Surface Treatment Specification:
Mil-c-83488, ty2 cl3 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-329-7659

Shear Bolt - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.