

View Online at <https://aerobasegroup.com/nsn/5306-01-329-7660>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.446 inches

**Fastener Length:**

Between 1.181 inches and 1.211 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.240 inches and 0.260 inches

**Width Between Flats:**

0.318 inches

**Extended Washer Diameter:**

Between 0.460 inches and 0.470 inches

**Extended Washer Thickness:**

Between 0.026 inches and 0.046 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.740 inches and 0.760 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Surface Finish:**

32.0 microinches threads

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Mil-c-83488, ty2 cl3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.