NSN 5306-01-329-7660



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-329-7660 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.446 inches **Fastener Length:** Between 1.181 inches and 1.211 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.240 inches and 0.260 inches Width Between Flats: 0.318 inches **Extended Washer Diameter:** Between 0.460 inches and 0.470 inches **Extended Washer Thickness:** Between 0.026 inches and 0.046 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response Mil-c-83488, ty2 cl3 military specification single treatment response

Surface Treatment: Aluminum and chromate **Surface Treatment Specification: Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5306-01-329-7660

Shear Bolt - Page 2 of 2



Unit	Of	Measure:
------	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.