## NSN 5306-01-329-7662

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-329-7662

**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.538 inches Fastener Length: Between 1.523 inches and 1.553 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.302 inches and 0.322 inches Width Between Flats: 0.383 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.035 inches and 0.055 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Thread Diameter:** 0.312 inches Grip Length: Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5306-01-329-7662

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

