

View Online at <https://aerobasegroup.com/nsn/5306-01-329-9720>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.691 inches and 0.741 inches

**Fastener Length:**

Between 1.513 inches and 1.543 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.383 inches and 0.403 inches

**Extended Washer Diameter:**

Between 0.807 inches and 0.817 inches

**Extended Washer Thickness:**

Between 0.063 inches and 0.073 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Head Minor Diameter:**

Between 0.485 inches and 0.500 inches

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 1.513 inches and 1.543 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Hole Configuration Style:**

Spline

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0