NSN 5306-01-330-0432

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-330-0432

| view Offiline at https://defobasegroup.com/nsi//3300-01-330-0432 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.553 inches and 0.603 inches |
| Fastener Length: |
| Between 1.938 inches and 1.968 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.188 inches and 0.203 inches |
| Width Between Flats: |
| Between 0.554 inches and 0.564 inches |
| Grip Diameter: |
| Between 0.3740 inches and 0.3745 inches |
| Thread Diameter: |
| 0.375 inches |
| Grip Length: |
| Between 1.365 inches and 1.385 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas6706 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5306-01-330-0432

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0