

View Online at <https://aerobasegroup.com/nsn/5306-01-330-0446>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.428 inches and 0.448 inches

Fastener Length:

Between 3.423 inches and 3.453 inches

Head Style:

Dished hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.313 inches

Grip Length:

Between 2.990 inches and 3.010 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

17100 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.990 inches first hole and 3.010 inches first hole

Material:

Stainless steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas2815 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0