NSN 5306-01-331-1261



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-331-1261 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.583 inches **Fastener Length:** Between 1.692 inches and 1.739 inches **Head Style:** Double hexagon **Head Height:** Between 0.247 inches and 0.267 inches Width Between Flats: Between 0.678 inches and 0.689 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Shank Unthreaded Hole Diameter:** 0.101 inches first hole and 0.111 inches first hole **Thread Diameter:** 0.437 inches **Grip Length:** 1.125 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.231 inches first hole **Product Name:** Navy special project Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-331-1261

Shear Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0