NSN 5306-01-331-1265

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-331-1265

	erobasegroup.com/nsn/5306-01-331-1265
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.578 inches	
Fastener Length:	
Between 3.938 inches	and 3.968 inches
Head Style:	
Dished hexagon	
Head Height:	
Between 0.188 inches	and 0.203 inches
Width Between Flats:	
Between 0.554 inches	and 0.564 inches
Grip Diameter:	
Between 0.3735 inches	and 0.3745 inches
Thread Diameter:	
0.375 inches	
Grip Length:	
Between 3.365 inches	and 3.385 inches
Thready Qty Per Inch	(tpi):
24	
Min. Tensile Strength	(psi):
160000 pounds per squ	lare inch
Material:	
Steel comp e4340 or s	teel comp 8740
Material Specification	:
Mil-s-5000 military spe	cification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium and chroma	e
Surface Treatment Sp	ecification:
Qq-p-416, type 2, class	2 federal specification single treatment response
Thread Series Design	ator:
Unjf	
Specification Data:	
80205-nas6606 profes:	sional/industrial association standard
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	

NSN 5306-01-331-1265

Close Tolerance Bolt - Page 2 of 2

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

