NSN 5306-01-331-5793



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-331-5793 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.709 inches **Fastener Length:** Between 2.005 inches and 2.052 inches **Head Style:** Double hexagon **Head Height:** Between 0.318 inches and 0.338 inches Width Between Flats: Between 0.865 inches and 0.877 inches **Grip Diameter:** Between 0.5610 inches and 0.5615 inches **Shank Unthreaded Hole Diameter:** 0.136 inches first hole and 0.146 inches first hole **Thread Diameter:** 0.562 inches **Grip Length:** 1.312 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.021 inches first hole **Product Name:** Navy special project Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-331-5793

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0