NSN 5306-01-331-6280

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-331-6280

Tilleau Class.
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.583 inches and 0.633 inches
Fastener Length:
Between 2.781 inches and 2.811 inches
Head Style:
Spline extended washer
Head Height:
Between 0.327 inches and 0.347 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Head Minor Diameter:
Between 0.448 inches and 0.455 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 2.178 inches and 2.198 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Aluminum and chromate
Surface Treatment Specification:
Mil-c-83488 type 2 cl 3 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-331-6280

Shear Bolt - Page 2 of 2



Ini	1 (Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.