NSN 5306-01-331-7193

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-331-7193 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.513 inches and 0.563 inches **Fastener Length:** Between 1.835 inches and 1.865 inches **Head Style:** Spline extended washer **Head Height:** Between 0.302 inches and 0.322 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.035 inches and 0.055 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Head Minor Diameter:** Between 0.383 inches and 0.389 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.302 inches and 1.322 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-331-7193

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0