

View Online at <https://aerobasegroup.com/nsn/5306-01-331-7335>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.286 inches

Fastener Length:

3.051 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.140 inches and 0.172 inches

Width Between Flats:

0.435 inches

Extended Washer Diameter:

0.435 inches

Extended Washer Thickness:

Between 0.015 inches and 0.025 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

First Diameter From Head:

Between 0.3119 inches and 0.3130 inches

Second Diameter From Head:

Between 0.187 inches and 0.197 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 2.666 inches and 2.686 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

2.765 inches

End Application:

Pacer dawn

Thread Diameter:

0.2500 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.891 inches first hole

Externally Relieved Body Diameter Quantity:

1

Material:

Stainless steel

Material Specification:

Ams6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas672 assn standard single treatment response or ams2416 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0