NSN 5306-01-331-7559

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-331-7559



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.583 inches and 0.633 inches

Fastener Length:

Between 2.155 inches and 2.185 inches

Head Style:

Spline extended washer

Head Height:

Between 0.327 inches and 0.347 inches

Extended Washer Diameter:

Between 0.691 inches and 0.701 inches

Extended Washer Thickness:

Between 0.044 inches and 0.064 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Head Minor Diameter:

Between 0.448 inches and 0.455 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.552 inches and 1.572 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-331-7559

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

