

View Online at <https://aerobasegroup.com/nsn/5306-01-331-8597>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.900 inches

**Fastener Length:**

Between 2.572 inches and 2.619 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.390 inches and 0.410 inches

**Width Between Flats:**

Between 1.052 inches and 1.064 inches

**Grip Diameter:**

Between 0.7485 inches and 0.7490 inches

**Shank Unthreaded Hole Diameter:**

0.136 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.750 inches

**Grip Length:**

1.688 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.366 inches first hole

**Product Name:**

Navy special project

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0