NSN 5306-01-331-9679

Shear Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-331-9679

Thread Direction:
Right-hand
Thread Length:
Between 0.313 inches and 0.333 inches
Fastener Length:
Between 0.620 inches and 0.650 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 3910 pounds per square inch
- " ·
3910 pounds per square inch
3910 pounds per square inch Material:
3910 pounds per square inch Material: Stainless steel
3910 pounds per square inch Material: Stainless steel Surface Treatment:
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification:
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1813 professional/industrial association standard
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1813 professional/industrial association standard Shelf Life:
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1813 professional/industrial association standard Shelf Life: N/a
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1813 professional/industrial association standard Shelf Life: N/a
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1813 professional/industrial association standard Shelf Life: N/a Unit Of Measure:
3910 pounds per square inch Material: Stainless steel Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1813 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: