NSN 5306-01-332-6473

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-332-6473 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.843 inches and 0.893 inches **Fastener Length:** Between 2.665 inches and 2.695 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.608 inches and 0.628 inches Width Between Flats: 0.775 inches **Extended Washer Diameter:** Between 1.040 inches and 1.050 inches **Extended Washer Thickness:** Between 0.672 inches and 0.697 inches **Shoulder Diameter:** 0.686 inches first shoulder and 0.687 inches first shoulder **Shoulder Length:** 1.802 inches first shoulder and 1.822 inches first shoulder **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-332-6473 Shoulder Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A003b0