## NSN 5306-01-332-6484



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-332-6484 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.621 inches and 0.761 inches **Fastener Length:** Between 6.731 inches and 6.751 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.435 inches Width Between Flats: 0.500 inches **Extended Washer Diameter:** Between 0.740 inches and 0.750 inches **Extended Washer Thickness:** 0.099 inches **Grip Diameter:** Between 0.436 inches and 0.437 inches **Thread Diameter:** 0.438 inches **Grip Length:** Between 5.990 inches and 6.010 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5306-01-332-6484

Shear Bolt - Page 2 of 2



Fiig:

A003b0