NSN 5306-01-332-6490



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-332-6490 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.633 inches **Fastener Length:** Between 1.617 inches and 1.664 inches **Head Style:** Double hexagon **Head Height:** Between 0.271 inches and 0.291 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Shank Unthreaded Hole Diameter:** 0.101 inches first hole and 0.111 inches first hole **Thread Diameter:** 0.500 inches **Grip Length:** 1.000 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.434 inches first hole **Product Name:** Navy special project Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-332-6490

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0