

View Online at <https://aerobasegroup.com/nsn/5306-01-332-8342>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.874 inches and 0.953 inches

**Fastener Length:**

Between 1.140 inches and 1.187 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.296 inches and 0.328 inches

**Width Between Flats:**

Between 0.865 inches and 0.877 inches

**Hole Diameter:**

Between 0.070 inches and 0.080 inches

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 0.234 inches and 0.266 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0