NSN 5306-01-333-5488

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-333-5488

| Thread | Class: |
|-----------|--|
| 3a | |
| | Direction: |
| Right-ha | |
| Thread I | |
| 0.454 ind | |
| | r Length: |
| | 3.564 inches and 3.594 inches |
| Head St | |
| Dished h | - |
| Head He | |
| | 0.188 inches and 0.203 inches |
| | etween Flats: |
| | 0.554 inches and 0.564 inches |
| Grip Dia | |
| | 0.3735 inches and 0.3745 inches |
| | Diameter: |
| 0.375 ind | |
| Grip Ler | - |
| | 3.115 inches and 3.135 inches |
| Thready | Qty Per Inch (tpi): |
| 24 | |
| | sile Strength (psi): |
| | bounds per square inch |
| | s Rating: |
| | xwell c and 40.0 rockwell c |
| Surface | Finish: |
| 32.0 mic | roinches threads |
| Material | |
| Steel co | np e4340 or steel comp 8740 |
| | Specification: |
| Mil-s-500 | 00 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard |
| 2nd mate | erial response |
| Surface | Treatment: |
| Cadmiur | n and chromate |
| Surface | Treatment Specification: |
| Qq-p-41 | 6, ty2 cl2 federal specification single treatment response |
| Thread | Series Designator: |
| Unjf | |
| Specific | ation Data: |
| 80205-na | as6206 professional/industrial association standard |
| Shelf Lif | e: |

N/a

NSN 5306-01-333-5488

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

