## NSN 5306-01-333-8050

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-333-8050

**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 1.005 inches Fastener Length: Between 2.505 inches and 2.535 inches **Head Style:** Spline extended washer **Head Height:** Between 0.552 inches and 0.572 inches **Extended Washer Diameter:** Between 1.153 inches and 1.163 inches **Extended Washer Thickness:** Between 0.080 inches and 0.100 inches Hole Diameter: Between 0.060 inches and 0.070 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches Head Minor Diameter: Between 0.673 inches and 0.688 inches **Thread Diameter:** 0.625 inches Grip Length: 1.500 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Hole Configuration Style: Spline Material: Steel comp h11 **Material Specification:** 

Ams6487 assn standard single material response



## NSN 5306-01-333-8050

Shear Bolt - Page 2 of 2



Surface Treatment: Cadmium and chromate Surface Treatment Specification: Mil-c-8837 ty2 cl2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0 Mil-std (military Standard): Mil-c-8837 spec.