## NSN 5306-01-333-9875



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-333-9875 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.908 inches **Fastener Length:** 2.408 inches **Head Style:** Spline extended washer **Head Height:** Between 0.440 inches and 0.460 inches **Extended Washer Diameter:** Between 0.922 inches and 0.932 inches

**Extended Washer Thickness:** 

Between 0.062 inches and 0.082 inches

**Grip Diameter:** 

Between 0.4985 inches and 0.4995 inches

**Head Minor Diameter:** 

Between 0.644 inches and 0.651 inches

**Thread Diameter:** 

0.500 inches

Grip Length:

Between 1.490 inches and 1.510 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Surface Finish:

32.0 microinches grip

Material:

Nickel alloy 718

**Material Specification:** 

Am 5662 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-01-333-9875

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0