

View Online at <https://aerobasegroup.com/nsn/5306-01-334-0512>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.439 inches and 0.469 inches

**Fastener Length:**

Between 5.439 inches and 5.469 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Grip Diameter:**

Between 0.3731 inches and 0.3737 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 4.990 inches and 5.010 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

5.276 inches first hole and 5.296 inches first hole

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Paint or dye threads only

**Color:**

Red threads

**Material:**

Titanium alloy uns r56400 fastener

**Material Specification:**

Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6406 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0