## NSN 5306-01-334-0514

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-334-0514 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.413 inches and 0.463 inches **Fastener Length:** Between 0.861 inches and 0.891 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r56400 fastener **Material Specification:** Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6405 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-01-334-0514

Shear Bolt - Page 2 of 2



Fiig:

A003b0