NSN 5306-01-334-0517

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-334-0517 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.741 inches **Fastener Length:** 5.366 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.435 inches Width Between Flats: 0.500 inches **Extended Washer Diameter:** Between 0.740 inches and 0.750 inches **Extended Washer Thickness:** 0.099 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Thread Diameter:** 0.437 inches **Grip Length:** Between 4.615 inches and 4.635 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-334-0517

Shear Bolt - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0