
# NSN 5306-01-334-1307

Shear Bolt - Page 1 of 2



AeroBase Group

# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.298 inches and 0.348 inches

#### Fastener Length:

Between 0.558 inches and 0.588 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.110 inches and 0.125 inches

#### Width Between Flats:

Between 0.367 inches and 0.376 inches

#### Hole Diameter:

Between 0.046 inches and 0.056 inches

## Locking Feature:

Patch threads or pellet threads or strip threads

#### **Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

## **Thread Diameter:**

0.190 inches

#### Grip Length:

Between 0.240 inches and 0.260 inches

## Hole Quantity:

3

#### Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hole Configuration Style:

Hexagon corners

## Surface Finish:

32.0 microinches threads

## Material:

Titanium alloy uns r56400 fastener

## **Material Specification:**

Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener

# **Thread Series Designator:**

Unjf

# NSN 5306-01-334-1307

Shear Bolt - Page 2 of 2



**Specification Data:** 

80205-nas 6403 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A003b0