# NSN 5306-01-334-1310

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-334-1310



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

Between 0.345 inches and 0.395 inches

#### Fastener Length:

Between 0.730 inches and 0.760 inches

#### **Head Style:**

Dished hexagon

#### Head Height:

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.429 inches and 0.439 inches

#### Locking Feature:

Patch threads or pellet threads or strip threads

#### **Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

#### **Thread Diameter:**

0.250 inches

## Grip Length:

Between 0.365 inches and 0.385 inches

### Thready Qty Per Inch (tpi):

28

### Min. Tensile Strength (psi):

160000 pounds per square inch

# Surface Finish:

32.0 microinches threads

### Material:

Plastic polyamide locking feature

### **Material Specification:**

Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

#### Surface Treatment:

Cadmium fastener and chromate fastener

### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response fastener

## **Thread Series Designator:**

Unjf

# **Specification Data:**

80205-nas6304 professional/industrial association standard

## Shelf Life:

N/a

# NSN 5306-01-334-1310

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

