# NSN 5306-01-334-1311

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-334-1311



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.345 inches and 0.395 inches

#### Fastener Length:

Between 0.855 inches and 0.885 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.429 inches and 0.439 inches

#### Locking Feature:

Patch threads or pellet threads or strip threads

#### **Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

#### **Thread Diameter:**

0.250 inches

### Grip Length:

Between 0.490 inches and 0.510 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Titanium alloy uns r56400 fastener

#### **Material Specification:**

Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas6404 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-01-334-1311

Shear Bolt - Page 2 of 2

Fiig: A003b0

