

View Online at <https://aerobasegroup.com/nsn/5306-01-334-6317>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.180 inches

Fastener Length:

Between 4.611 inches and 4.641 inches

Head Style:

Spline extended washer

Head Height:

Between 0.590 inches and 0.610 inches

Extended Washer Diameter:

1.389 inches

Extended Washer Thickness:

Between 0.098 inches and 0.118 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Head Minor Diameter:

Between 0.797 inches and 0.812 inches

End Application:

Pacer dawn

Thread Diameter:

0.7500 inches

Grip Length:

Between 3.428 inches and 3.448 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Special Features:

Hole drilled in top center of head, 0.540/0.580 in. Diameter x 0.146 in. Nomdeep

Material:

Steel

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type ii, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.