

View Online at <https://aerobasegroup.com/nsn/5306-01-334-6318>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.012 inches

Fastener Length:

Between 1.880 inches and 1.910 inches

Head Style:

Spline extended washer

Head Height:

Between 0.552 inches and 0.572 inches

Extended Washer Diameter:

1.158 inches

Extended Washer Thickness:

Between 0.080 inches and 0.100 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Head Minor Diameter:

Between 0.673 inches and 0.688 inches

End Application:

Pacer dawn

Thread Diameter:

0.6250 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Spline

Surface Finish:

32.0 microinches grip

Special Features:

Hole drilled in top center of head, 0.470/0.510 in. Diameter x 0.180 in. Nomdeep

Material:

Steel

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type ii, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.