## NSN 5306-01-334-6320

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-334-6320

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.578 inches
Fastener Length:
Between 2.125 inches and 2.155 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
0.559 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole and 0.116 inches first hole
End Application:
Pacer dawn
Thread Diameter:
0.3750 inches
Grip Length:
Between 1.552 inches and 1.572 inches
Thready Qty Per Inch (tpi):
24
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.943 inches first hole
Special Features:
Shot peened prior to chromium plate; all surfaces not chromium plated are cadmium plated
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-334-6320

Close Tolerance Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

