NSN 5306-01-334-6322

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-334-6322

Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 1.075 inches Fastener Length: Between 2.067 inches and 2.097 inches **Head Style:** Spline extended washer **Head Height:** Between 0.552 inches and 0.572 inches **Extended Washer Diameter:** 1.158 inches **Extended Washer Thickness:** Between 0.080 inches and 0.100 inches Hole Diameter: Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches Head Minor Diameter: Between 0.673 inches and 0.688 inches **End Application:** Pacer dawn **Thread Diameter:** 0.6250 inches Grip Length: Between 1.052 inches and 1.072 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 18 Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Hole Configuration Style: Spline Surface Finish: 32.0 microinches grip **Special Features:** Hole drilled in top center of head, 0.500 in. Diameter x 0.185 in. Deep approx

NSN 5306-01-334-6322

Close Tolerance Bolt - Page 2 of 2



Material:

Steel

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type ii, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.