

View Online at <https://aerobasegroup.com/nsn/5306-01-334-6325>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.323 inches

**Fastener Length:**

Between 0.496 inches and 0.526 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

0.372 inches

**Hole Diameter:**

Between 0.046 inches and 0.056 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**End Application:**

Pacer dawn

**Thread Diameter:**

0.1900 inches

**Grip Length:**

Between 0.178 inches and 0.198 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Hole Configuration Style:**

Hexagon corners

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.347 inches first hole

**Material:**

Steel

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0