

View Online at <https://aerobasegroup.com/nsn/5306-01-334-6648>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

1.166 inches

Head Style:

Spline extended washer

Head Height:

Between 0.302 inches and 0.322 inches

Extended Washer Diameter:

Between 0.575 inches and 0.595 inches

Extended Washer Thickness:

Between 0.035 inches and 0.056 inches

Hole Diameter:

Between 0.049 inches and 0.061 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Head Minor Diameter:

Between 0.383 inches and 0.389 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.552 inches and 0.572 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Double hexagon flats

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 type 2, cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.