

View Online at <https://aerobasegroup.com/nsn/5306-01-334-7364>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.402 inches and 0.438 inches

Fastener Length:

Between 1.293 inches and 1.313 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.126 inches and 0.141 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Locking Feature:

Detent ring grip

Grip Diameter:

Between 0.2483 inches and 0.2492 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.875 inches and 0.891 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

Surface Finish:

63.0 microinches bearing surface of head

Special Features:

Retaining element on shank

Material:

Steel comp 630

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0