
## NSN 5306-01-334-7892

Shear Bolt - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

#### Thread Length:

Between 0.345 inches and 0.395 inches

#### Fastener Length:

Between 0.980 inches and 1.010 inches

#### Head Style:

Dished hexagon

#### Head Height:

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.429 inches and 0.439 inches

#### Locking Feature:

Patch threads or pellet threads or strip threads

## Grip Diameter:

Between 0.2490 inches and 0.2495 inches

#### Thread Diameter:

0.250 inches

## Grip Length:

Between 0.615 inches and 0.635 inches

## Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Surface Finish:

32.0 microinches threads

## Material:

Plastic polyamide locking feature

## Material Specification:

Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

## Thread Series Designator:

Unjf

## **Specification Data:**

80205-nas6304 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-01-334-7892

Shear Bolt - Page 2 of 2

Fiig: A003b0

