## NSN 5306-01-334-7905

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-334-7905 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** Between 2.204 inches and 2.234 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: 0.497 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **End Application:** Pacer dawn **Thread Diameter:** 0.3125 inches **Grip Length:** Between 1.740 inches and 1.760 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.038 inches first hole **Special Features:** Shot peened prior to chromium plate; all surfaces not chromium plated are cadmium plated Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5306-01-334-7905

Close Tolerance Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0