

View Online at <https://aerobasegroup.com/nsn/5306-01-334-7906>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.345 inches

Fastener Length:

Between 0.830 inches and 0.860 inches

Head Style:

Dished hexagon

Head Height:

Between 0.110 inches and 0.125 inches

Width Between Flats:

0.372 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

End Application:

Pacer dawn

Thread Diameter:

0.1900 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Thready Qty Per Inch (tpi):

32

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.681 inches first hole

Special Features:

Shot peened prior to chromium plate; all surfaces not chromium plated are cadmium plated

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0