

View Online at <https://aerobasegroup.com/nsn/5306-01-334-7908>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.041 inches

Fastener Length:

Between 2.026 inches and 2.056 inches

Head Style:

Dished hexagon

Head Height:

Between 0.375 inches and 0.390 inches

Width Between Flats:

1.058 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

End Application:

Pacer dawn

Thread Diameter:

0.7500 inches

Grip Length:

Between 0.990 inches and 1.010 inches

Thready Qty Per Inch (tpi):

16

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.789 inches first hole

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response or ams6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.