

View Online at <https://aerobasegroup.com/nsn/5306-01-334-7911>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.940 inches

Fastener Length:

Between 2.685 inches and 2.715 inches

Head Style:

Spline extended washer

Head Height:

Between 0.495 inches and 0.515 inches

Extended Washer Diameter:

1.042 inches

Extended Washer Thickness:

Between 0.071 inches and 0.091 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Head Minor Diameter:

Between 0.610 inches and 0.625 inches

End Application:

Pacer dawn

Thread Diameter:

0.5625 inches

Grip Length:

Between 1.740 inches and 1.760 inches

Thready Qty Per Inch (tpi):

18

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Special Features:

Hole drilled in top center of head, 0.410/0.450 in. Diameter x 0.164 in. Nomdeep

Material:

Steel

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type ii, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.