

View Online at <https://aerobasegroup.com/nsn/5306-01-334-7913>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.180 inches

**Fastener Length:**

Between 3.861 inches and 3.891 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.590 inches and 0.610 inches

**Extended Washer Diameter:**

1.389 inches

**Extended Washer Thickness:**

Between 0.098 inches and 0.118 inches

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**Head Minor Diameter:**

Between 0.797 inches and 0.812 inches

**End Application:**

Pacer dawn

**Thread Diameter:**

0.7500 inches

**Grip Length:**

Between 2.678 inches and 2.698 inches

**Thready Qty Per Inch (tpi):**

16

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Hole drilled in top center of head, 0.540/0.580 in. Diameter x 0.146 in. Nomdeep

**Material:**

Steel

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837, type ii, class 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.