

View Online at <https://aerobasegroup.com/nsn/5306-01-334-8552>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.468 inches

Fastener Length:

Between 5.827 inches and 5.874 inches

Head Style:

Hexagon

Head Height:

Between 0.234 inches and 0.266 inches

Width Between Flats:

Between 0.740 inches and 0.752 inches

Grip Diameter:

Between 0.4986 inches and 0.4991 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

5.375 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.625 inches first hole

Surface Finish:

32.0 microinches grip

Product Name:

Navy special project

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium head and chromate head

Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response threads

Thread Series Designator:

Unjf

Specification Data:

80205-nas464 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0