## **NSN 5306-01-335-0020** Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-335-0020	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.298 inches and 0.348 inches	
Fastener Length:	
Between 0.870 inches and 0.900 inches	
Head Style:	
Dished hexagon	
Head Height:	
Between 0.110 inches and 0.125 inches	
Width Between Flats:	
Between 0.367 inches and 0.376 inches	
Hole Diameter:	
Between 0.046 inches and 0.056 inches	
Locking Feature:	
Patch threads or pellet threads or strip threads	
Grip Diameter:	
Between 0.1890 inches and 0.1895 inches	
Thread Diameter:	
0.190 inches	
Grip Length:	
Between 0.552 inches and 0.572 inches	
Hole Quantity:	
3	
Hole Type:	
Drilled	
Thready Qty Per Inch (tpi):	
32	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Hole Configuration Style:	
Hexagon corners	
Surface Finish:	
32.0 microinches threads	
Material:	
Titanium alloy uns r56400 fastener	
Material Specification:	
Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener	
Thread Series Designator:	

Unjf

## NSN 5306-01-335-0020

Shear Bolt - Page 2 of 2



Specification D	ata:
-----------------	------

80205-nas6403 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0